

M200

Weighing Indicator



FEATURES

- Up to 1/15,000 display resolution
- High Speed 24bits AD; Display reading speed faster
- AC / DC switching function (Built-in rechargeable battery)
- LED display (Weight-6 digits); Full range tare; Auto zero tracking
- Low power indication
- Simple counting; Hold function; Accumulating function
- Check mode Lo / Hi / OK
- LED Lo / Hi / OK indication
- Selectable units: Kilogram (kg) and pound (lb)
- Power-saving mode (LED only)

(Optional Features):

- RS232C: Easily transmitting data to PC or printing
- Sleeve connecting stand

PRODUCT SPECIFICATIONS

Model:	M200
A/D Conversion Speed	24 bits
Operating Temperature	0°C ~ 40°C (32°F ~ 104°F)
Application	Can be connected to most types of platforms
Max. Connection Number of Load Cell	1-4 at 350 ohm
Load Cell Connection Mode	5 Pin-DIN Connector
Indicator Dimensions	235 x 165 x 127 mm (W x H x D)
Division	0.01kg to 150kg
Display	LED 6 digits, Height 25mm
Display Range	Up to 1/15,000 display resolution
Transmission Distance	RS232 ≤ 30m
AC Power Supply	AC 110V/220V (±10%)
DC Power Supply	DC 6V / 4Ah rechargeable battery

The technical data given here serve only as a product description and must not be interpreted as guaranteed characteristics in the Legal sense.

3193 N, Drinkwater Blvd, P.O.Box 32662, Scottsdale, AZ 85251, U.S.A

Phone: # 480-240-1299

Fax: # 480-240-1300

Email: Info@themaxtechnologies.com

Max Technologies reserves the right make changes to the technology, features, specification and design of the equipment without notice.