

M600

Weighing Indicator (Stainless Steel Version)



FEATURES

- All Stainless Steel Housing
- Wash Down Design According To IP 65
- Up To 1/30000 Display Resolution
- User Friendly Setup, Calibration And Operation Procedures
- Maximum Number Of Load Cells: 8 X 350 Ohm
- Low Battery And Charge Status Indicator
- Table Stand, Backlight, And Built-In Rechargeable Battery Included
- Large 50mm (2 Inch) Backlit Display
- Configurable Divisions And Capacity
- Auto Zero Tracing
- Password Protected
- Low Battery Indicator And Charge Status Light

PRODUCT SPECIFICATIONS

Name	M600
A/D Converter	24 bit high speed A/D converter with over 1,000,000 internal counts
Weighing Units/ functions	lb, kg, g, metric ton
Display Resolution	MAX : 30000
Min. Input Per Display Resolution	0.1 μ v
A/D Conversion Speed	50 times/sec
Display Speed	25/sec
Span Adjustment	0.6 mv/v to 4mv/v full scale
Zero Drift	0.3 μ v/ $^{\circ}$ c (typ.)
Span Drift	\pm 8ppm / $^{\circ}$ c (typ.)
Non-Linearity	<0.0033% R.O
Load Cell Excitation	DC 5v (up to 8x350 ohm load cells)
Power Supply	AC 110/230v \pm 10%, 50/60 Hz rechargeable battery 6v,
Operation Environment	0 $^{\circ}$ C ~ 40 $^{\circ}$ C (32 $^{\circ}$ F ~ 104 $^{\circ}$ F) non-condensed R.H. \leq 90%

The technical data given here serve only as a product description and must not be interpreted as guaranteed characteristics in the Legal sense.

3193 N, Drinkwater Blvd, P.O.Box 32662, Scottsdale, AZ 85251, U.S.A

Phone: # 480-240-1299

Fax: # 480-240-1300

Email: Info@themaxtechnologies.com

Max Technologies reserves the right make changes to the technology, features, specification and design of the equipment without notice.