

# M 10

## Weighing Indicator



### FEATURES

- High Resolution Till 1/30,000
- Big Red LED Display
- Drive Up to 4x350 Load Cells
- Zero/Tare Function
- Counting Function
- Accumulating Function
- Response Speed Adjustable
- Zero Range Programmable
- G Value (Gravity) Adjusting

### Optional Accessories

- RS 232c
- SS Braket

Model	M 10
Power	100-240V 50/60-10V Adaptor Rechargeable
Excitation Voltage	DC5V 1-4-350
Analog Input Singnal	0.6m V/V-3m V/V
A/D Rate	20 time/Second
Display Resolution	1/3,000- 1/30,000
Display	LED 31mm)
Units	Kg.lb.g.oz.etc
Output	RS 232c(Optional )
Operating Temperature	0°C-40°C
Storage Temperature	-25°C to +55°C
Relative Humidity	non-Condensing
Protection	IP54
Packing Size	80x38x55cm
Housing	ABS

The technical data given here serve only as a product description and must not be interpreted as guaranteed characteristics in the Legal sense.

3193 N, Drinkwater Blvd, P.O.Box 32662, Scottsdale, AZ 85251, U.S.A

Phone: # 480-240-1299

Fax: # 480-240-1300

Email: Info@themaxtechnologies.com

Max Technologies reserves the right make changes to the technology, features, specification and design of the equipment without notice.