

Weighing Indicator



FEATURES

- Multiple weighing units: (lb/kg)
 - Gross/Tare/Pre-Set Tare/Zero
 - Multiple Hold functions
 - Count weighing
 - Overload / Underload
 - Power saving mode
 - Automatic date and time update
 - Ability to modify gravity based on different geographical locations
 - Connects to a remote display
 - NTEP approved for 5,000 divisions
 - 1" LED display with backlight
 - Operates on 110V AC adapter (included)
 - Full Duplex RS-232 Serial Port
 - Drives up to 6 350 Ω load cells
- Stainless steel

(Optional Features):

- RS232C: Easily transmitting data to PC or printing
- Sleeve connecting stand

PRODUCT SPECIFICATIONS

Model:	
Display	LED 1-inch x 6-digit numeric
Units	Lb, kg (primary); oz, g (secondary)
Accuracy Class	5000 e
Resolution	120,000 dd industrial; 10,000 dd HB44
Excitation Voltage	5V DC
Excitation circuit	5 VDC, 4 wire connections
Load Cell	6 load cells of 350 Ω maximum
Load Cell Excitation	5 \pm 0.5VDC
Display Resolution	30,000 ; ADC: 2,000,000
Input voltage	-30 to +30mV DC
Analog Signal Input Range	1mV to 3mV
Serial Port	RS-232 C

The technical data given here serve only as a product description and must not be interpreted as guaranteed characteristics in the Legal sense.

3193 N, Drinkwater Blvd, P.O.Box 32662, Scottsdale, AZ 85251, U.S.A

Phone: # 480-240-1299

Fax: # 480-240-1300

Email: Info@themaxtechnologies.com

Max Technologies reserves the right make changes to the technology, features, specification and design of the equipment without notice.