

## Digital Weighing Indicator



### FEATURES

- Multiple weighing units: (lb/kg)
- Scale Debugging
- Printing Parameter
- Communication Setting
- Scale Platform Corner Adjusting
- Scale Weight Calibration
- Overload / Underload
- Automatic Net Connection
- Single Load cell distribute Address
- Display long time working
- 1" LED display
- Full Duplex RS-232 Serial Port

### (Optional Features):

- Easily transmitting data to PC
- Password Setting
- Number of connections

## PRODUCT SPECIFICATIONS

<b>Model:</b>	<b>M800</b>
<b>Display</b>	<b>7-digit ultra-bright LED digital tube</b>
Units	Lb, kg (primary); oz, g (secondary)
Connection mode:	RS485 mode, four-wire and six-wire compatible
Communication distance	1000 meters
Number of connections	1 to 16
Sensor power supply	DC 10V, 0.8A (Max)
Clock	Automatic leap year and leap month,
Signal	20mA current loop, serial output, transmission
Standard configuration	RS232/RS485 adaptive; 2. RS232
Power supply	AC-187-242V,49-51HC
DC power supply	External 12V battery power supply

The technical data given here serve only as a product description and must not be interpreted as guaranteed characteristics in the Legal sense.

3193 N, Drinkwater Blvd, P.O.Box 32662, Scottsdale, AZ 85251, U.S.A

Phone: # 480-240-1299

Fax: # 480-240-1300

Email: [Info@themaxtechnologies.com](mailto:Info@themaxtechnologies.com)

Max Technologies reserves the right make changes to the technology, features, specification and design of the equipment without notice.